

Document Title	M101GWN9 R2 Product Information			Page No.	1/23
Document No.		Issue date	2013/07/17	Revision	01

Product Information

To:

Product Name: M101GWN9 R2

Document Issue Date: 2013/07/17

Customer		InfoVision Optoelectronics
<u>SIGNATURE</u>		SIGNATURE REVIEWED BY QA
		PREPARED BY FAE
Please return 1 copy for your confirmation with your signature and comments		
your signature and comments.	L	

Note: 1. Please contact InfoVision Company before designing your product based on this product.
 2. The information contained herein is presented merely to indicate the characteristics and performance of our products. No responsibility is assumed by IVO for any intellectual property claims or other problems that may result from application based on the module described herein.

FQ-7-30-0-009-03C

□ 昆山龙腾光电有限公司 ■ InfoVision Optoelectronics(Kunshan)Co.,LTD. ■ Document Title M101GWN9 R2 Product Information Page No. 2/23

Document Title	M101GWN9 R2 Product Information			Page No.	2/23
Document No.		Issue date	2013/07/17	Revision	01

Revision	Date	Page	Old Description	New Description	Remark
00	2013/07/17	all		First issue.	
					\bigcirc

All rights strictly reserved reproduction or issue to third parties in any form what ever is not permitted without written authority from the proprietor.

- ARRAN

IVO

Document Title	M101GWN9 R2 Product Information			Page No.	3/23
Document No.		Issue date	2013/07/17	Revision	01

Contents

1.0 General Descriptions Introduction	4
2.0 Absolute Maximum Ratings	
4.0 Optical Characteristics	
5.0 Backlight Characteristics (Reference)	
6.0 Electrical Characteristics	
7.0 Interface Timings	
8.0 Power Consumption	
9.0 Power ON/OFF Sequence	
10.0 Reliability Test Criteria	
11.0 Mechanical Characteristics	
12.0 Package Specification	
13.0 Lot Mark	
14.0 General Precaution	

- ORTHUR AND

Document Title	M101GWN9 R2 Product Information			Page No.	4/23
Document No.		Issue date	2013/07/17	Revision	01

1.0 General Descriptions Introduction

1.1 Introduction

The M101GWN9 R2 is a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. It is composed of a TFT LCD panel, column driver and row driver circuit. This TFT LCD has a 10.1-inch diagonally measured active display area with WSVGA resolution (1024 horizontal by 600 vertical pixels array).

1.2 Features

- 10.1" TFT LCD Panel
- Supported WSVGA resolution
- Compatible with RoHS standard

1.3 Product Summary

Items	Specifications	Unit
Screen Diagonal	10.1	Inch
Active Area	222.72(H) x 125.28(V)	mm
Pixels H x V	1024(RGB) x600	-
Pixel Pitch	0.2175(H) x 0.2088(V)	mm
Pixel Arrangement	RGB Vertical Stripe	-
Display Mode	Normally White	-
Contrast Ratio	(500) (Typ.)	-
Response Time	16 (Typ.)	ms
Input Voltage	+3.3 (Typ.)	V
Weight	TBD	g
Outline Dimension (H x V x D)	235(Typ.) x 143(Typ.) x 7.54(Typ.)	mm
Electrical Interface (Logic)	LVDS	-
Support Color	16.7M	-
Surface Treatment	Anti-glare, Hard-Coating (3H)	-



1.4 Functional Block Diagram

Figure 1 shows the functional block diagram of the LCD module.

YVCC Connector(40Pin) Fuse V_LED Fuse Charge VGH. Pump *2 VIN Gate DC/DC Driver IC LVDS Signal Charge VGL LED _Driver XVCC Pump AVDD Vcom **Control Signal** Gamma Connector(9Pin) V1~V14 Vcom Source driver IC Ba

Figure 1 Block Diagram

Document Title	M101GWN9 R2 Product Information			Page No.	6/23
Document No.		Issue date	2013/07/17	Revision	01

2.0 Absolute Maximum Ratings

Table 1 Electrical Absolute Rating

ITEM	SYMBOL	MIN.	MAX.	UNIT	REMARK
Supply Voltage	V _{IN}	-0.3	3.96	V	Logic power supply voltage
Supply vollage		-0.3	12	V	LED Driver Vin
Power Supply Fuse			1.5	^	Vin from10% \sim 90% , rise
Current Setting	IFUSE	-	1.5	A	time 500us
Input Signal	Vs	-	3.6	V	LVDS signals
EN/PWM Voltage	V_{PWM}	-0.3	12	V	EN/PWM Voltage

Table 2 Absolute Ratings of Environment

... <i>.</i> . <i>.</i> . <i>.</i> ..								
Item	Symbol	Min.	Max.	Unit	Conditions			
Operating Temperature	TOP	-20	70	Ĉ				
Operating Humidity	HOP	10	85	%RH	(1) (2)			
Storage Temperature	TST	-30	80	$^{\circ}\mathrm{C}$	(1),(2)			
Storage Humidity	HST	10	95	%RH				

Note (1) There is no display function fail occurred, all the cosmetic specification is judged before the reliability stress. The criteria is fit by IVO provided IIS.

(2) The storage /operating temperature. Maximum Wet-Bulb should be 39 degree C. There is no condensation on the panel surface.



Document Title	M101GWN9 R2 Product Information			Page No.	7/23
Document No.		Issue date	2013/07/17	Revision	01

3.0 Pixel Format Image

Figure 2 shows the relationship of the input signals and LCD pixel format image.

Figure 2 Pixel Format



□ 昆山龙腾光电有限公司 InfoVision Optoelectronics(Kunshan)Co.,LTD. Document Title M101GWN9 R2 Product Information Page No. 8/23

Document Title	M101GWN9 R2 Product Information			Page No.	8/23
Document No.		Issue date	2013/07/17	Revision	01

4.0 Optical Characteristics

The optical characteristics are measured under stable conditions as following notes

Item	Conditions		Min.	Тур.	Max.	Unit	Note
	Llorizontol	θ∟	(70)	(80)	-		
Viewing Angle	Honzontai	θ _R	(70)	(80)	-	dograa	(1) (2) (2)
(CR>10)	Vertical	θ _T	(70)	(80)	-	uegree	(1),(2), (3)
	Vertical	θ _Β	(70)	(80)	-		
Contrast Ratio	Center		-	(500)	-		(1),(2), (4)
	Rising		-	TBD	\odot	ms	
Response Time	Falling		-	TBD	<u>)</u>	ms	(1),(2),(5)
	Rising + Falling		-+(16	-	ms	
	NTSC		X	(45)	-	%	
	Red x			TBD		-	
	Red y	- C		TBD		-	
Chromaticity	Green x	XK	Тур.	TBD	Тур.	-	
	Green y 🕻		-0.03	TBD	-0.03	-	(1),(2)
	Blue x			TBD		-	
	Blue y	•		TBD		-	
	White x		(0.255)	(0.305)	(0.355)	-	
	White y		(0.275)	(0.325)	(0.375)	-	
White Luminance	Center		-	(350)	-	cd/m^2	(1),(2),(6)
Luminance Uniformity	9Points		(75)	(80)	-	%	(1),(2),(6)

Table 3 Optical Characteristics

Note (1) Measurement Setup:

The LCD module should be stabilized at given temperature $(25^{\circ}C)$ for 15 minutes to Avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting backlight for 15 minutes in a windless room.

昆山龙腾光电有限公司 ■ InfoVision Optoelectronics (Kunshan) Co.,LTD.							
Document Title	M101GWN9 R2 Product Information			Page No.	9/23		
Document No.		Issue date	2013/07/17	Revision	01		



Figure 3 Measurement Setup

Note (2) The LED input parameter setting as:

VLED: 5V;

PWM_LED: Duty 100 %

Note (3) Definition of Viewing Angle





Note (4) Definition of Contrast Ratio (CR)

The contrast ratio can be calculated by the following expression

Contrast Ratio (CR) = L255 / L0

L255: Luminance of gray level 255, L0: Luminance of gray level 0

Note (5) Definition of Response Time (T_R, T_F)

昆山龙腾光电有限公司 ■ InfoVision Optoelectronics (Kunshan) Co.,LTD.						
Document Title	M101GWN9 R2 Product Information			Page No.	10/23	
Document No.		Issue date	2013/07/17	Revision	01	

Figure 5 Definition of Response Time



Note (6) Definition of Brightness Luminance

Luminance Uniformity=
$$\frac{(MinLuminanceof 9 points)}{(MaxLuminanceof 9 points)} \times 100\%$$

Figure 6 Measurement Locations



<th colspan="4" <th colspan="4" <th colspan="4" <th colspa="4" <th colspan="4" <th colspa="4"

5.0 Backlight Characteristics (Reference)

ITEM		UNIT	MIN	TYP	MAX	CONDITION
VIN_LEI	C	V	4.5	5	5.5	DUTY=100%
I _{VIN_LED}		mA	-	-	586	V_LED=4.5V , η=85%
F _{DIM}		Hz	200	-	1K	
DUTY		%	5	-	100	
FN/PW/M	VIH	V	2	-	5	<u> </u>
	VIL	V	0	-	0.5	-
Vout		V	11.6	13.2	14	-
I _{OUT}		mA	-	159	-	-
LT		Hours	(30,000)	x 0	-	LED Life Time

Table 4 LED driver Input and Output Specifications

Note: The LED life time define as the estimated time to 50% degradation of initial luminous.

昆山龙腾光电有限公司 InfoVision Optoelectronics (Kunshan) Co.,LTD.						
Document Ti	Document Title M101GWN9 R2 Product Information			Page No.	12/23	
Document N	lo.		Issue date	2013/07/17	Revision	01

6.0 Electrical Characteristics

Table 5 Connector Name / Designation

Item	Description
Connector	MSAK24025P40D
Continent	tial

WO

Document Title	M101GWN9 R2 Product Information			Page No.	13/23
Document No.		Issue date	2013/07/17	Revision	01

Table 6 Pin Assignment

Pin #	Signal Name	Description	Remarks
1	BIST	BIST MODE SELECT(High Enable)	FOR INTERNAL TEST
2	VDD	LCD power supply (Typ. +3.3V)	
3	VDD	LCD power supply (Typ. +3.3V)	
4	V_EDID	EDID power supply	
5	NC	No connection	
6	CLK_EDID	EDID CLK signal	
7	Data_EDID	EDID Data signal	
8	LVDS input 0-	LVDS CH0 data signal(-) $\$ R0 \sim R5 $\$ G0	
9	LVDS input 0+	LVDS CH0 data signal(+) \cdot R0 \sim R5 \cdot G0	
10	GND	GND	
11	LVDS input 1-	LVDS CH1 data signal(-) \cdot G1 \sim G5 \cdot B0 \cdot B1	
12	LVDS input 1+	LVDS CH1 data signal(+) \cdot G1 \sim G5 \cdot B0 \cdot B1	
13	GND	GND	
14	LVDS input 2-	LVDS CH2 data signal(-) \cdot B2 \sim B5 \cdot DE	
15	LVDS input 2+	LVDS CH0 data signal(+) B2~B5 DE	
16	GND	GND	
17	LVDS CLK -	LVDS CLK data signal(-)	
18	LVDS CLK +	LVDS CLK data signal(+)	
19	GND	GND	
20	IVDS input 3-	LVDS CH3 data signal(-) R6~R7 G6~G7	
20		B6~B7	
21	LVDS input 3+	LVDS CH3 data signal(-)	
	Evelo input o	B6~B7	
22	GND	GND	
23	NC	No connection	
24	NC	No connection	
25	GND	GND	
26	NC	No connection	
27	NC	No connection	
28	GND	GND	
29	NC	No connection	
30	NC	No connection	
31	GND	GND	

All rights strictly reserved reproduction or issue to third parties in any form what ever is not permitted without written authority from the proprietor.

IVO

昆山龙腾光电有限公司 InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M101GWN9 R2 Product Information			Page No.	14/23
Document No.		Issue date	2013/07/17	Revision	01

32	GND	GND	
33	GND	GND	
34	NC	No connection	
35	PWM	LED dimming signal	
36	LED_EN	LED Enable signal	
37	NC	No connection	
38	VLED	LED power supply (Typ. 5V)	
39	VLED	LED power supply (Typ. 5V)	
40	VLED	LED power supply (Typ. 5V)	

A

OHHHMM



Document Title	M101GWN9 R2 Product Information			Page No.	15/23
Document No.		Issue date	2013/07/17	Revision	01

Table 7 Electrical Characteristics

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS
System Power Supply	·					
Input Power Supply Voltage	V _{IN}	3.0	3.3	3.6	V	
Input Power Supply Current	I _{VIN}	-	-	217	mA	Black pattern [,] 60Hz
Input Inrush Current	I _{RUSH}	-	-	1.5	А	0.5ms rise time (10%~90%)
Input Power Voltage Ripple	V _{RPL}	-	-	200	mV	Vp-p
LED Power Supply						J.
Input Power Supply Voltage	$V_{\text{LED-IN}}$	4.5	5	5.5	V	
Input Power Supply Current	I _{IN}	-	-	586	mA	V_LED=4.5V,η=85%
FN/PWM	VH	2.0		5.0	V	
	VL	0	\mathcal{F}	0.5	V	
LVDS Signals		X				
Differential Input High Threshold	V _{th})	-	+100	mV	V _{cm} =+1.2V
Differential Input Low Threshold	Vti	-100	-	-	mV	V _{cm} =+1.2V
Magnitude Differential Input Voltage	[V _{id}]	200	-	600	mV	
Common Mode Voltage	V _{cm}	1.0	1.2	1.4	V	V_{th} - V_{tl} = 200mV
Common Mode Voltage Offset	ΔV_{cm}	-50	-	+50	mV	V_{th} - V_{tl} = 200mV
EDID Power Supply		-		<u>.</u>	<u>.</u>	
Input Power Supply Voltage	V_EDID	3.0		3.6	V	

Note: A. Input signals shall be low or Hi-Z state when VIN is off.

- B. All electrical characteristics for LVDS signal are defined and shall be measured at the interface connector of LCD.
- C. White Pattern at 3.3V driving voltage.



Document Title	M101GWN9 R2 Produc	Page No.	16/23		
Document No.		Issue date	2013/07/17	Revision	01

7.0 Interface Timings

7.1 Timing Characteristics

Table 8 Interface Timings

Synchronization Method : DE only

Parameter	Symbol	Unit	Min.	Тур.	Max.
LVDS Clock Frequency <single></single>	\mathbf{f}_{dck}	MHz	45	51.2	65
H Total Time	T_{hp}	clocks	1,324	1,344	1,364
H Active Time	HA	clocks	1,024	1,024	1,024
H Blanking Time	TH_{BLANK}	clocks	300	320	340
V Total Time	T_{vp}	lines	615	635	645
V Active Time	VA	lines	600	600	600
V Blanking Time	TV_{BLANK}	lines	15	35	45
V Frequency	f_v	Hz	55	60	65

Figure 7 DE-only timing mode



7.2 Timing Diagram of Interface Signal





Document Title	M101GWN9 R2 Produc	Page No.	17/23		
Document No.		Issue date	2013/07/17	Revision	01

8.0 Power Consumption

Input power specifications are as follows.

Table 9 Power Consumption

Item	Symbol	Min.	Тур.	Max.	Units	Note
Input Power Supply Voltage	V _{IN}	3.0	3.3	3.6	V	
Input Power Supply Current	I _{VIN}	-	-	217	mA	Black pattern [,] 60Hz
Input Inrush Current	I _{RUSH}	-	-	1.5	A	0.5ms rise time (10%~90%)
Input Power Voltage Ripple	V _{RPL}	-	-	200	mV	Vp-p

昆山龙腾光电有限公司 InfoVision Optoelectronics (Kunshan) Co.,LTD.								
Document T	Document Title M101GWN9 R2 Product Information			Page No.	18/23			
Document N	No.		Issue date	2013/07/17	Revision	01		

9.0 Power ON/OFF Sequence

Figure 9 Power Sequence



B山龙腾光电有限公司 InfoVision Optoelectronics(Kunshan)Co.,LTD. Document Title M101GWN9 R2 Product Information Page No. 19/23 Document No. Issue date 2013/07/17 Revision 01

Table 10 Power Sequencing Requirements

Parameter	Symbol	Unit	min	Тур.	max
VDD rising Time	T1	ms	0.5		10
VDD Good to Signal Valid	T2	ms	30		90
Signal Valid to Backlight on	Т3	ms	200		X
Backlight Power on time	T4	ms	0.5		N
Backlight VDD Good to System PWM on	T5	ms	10		
System PWM on to Backlight Enable on	Т6	ms	10	X	-
Backlight Enable off to System PWM off	T7	ms	0		
System PWM off to B/L Power Disable	Т8	ms	10		
Backlight Power off time	Т9	ms		10	30
Backlight off to signal Disable	T10	ms	200		
Signal Disable to Power Down	T11	ms	0		50
VDD Falling Time	T12	ms	1	10	30
Power Off	Т13	ms	500		

ORTHORN

Document Title	M101GWN9 R2 Product Information				20/23
Document No.		Issue date	2013/07/17	Revision	01

10.0 Reliability Test Criteria

Table 11 Reliability Test Criteria

Items	Required Condition	Note
High Temperature Operating Test	70°C, 300hrs	×
Low Temperature Operating Test	-20℃, 300hrs	
High Temperature Storage Test	80°C, 300hrs	
Low Temperature Storage Test	-30℃, 300hrs	
High Temperature/High Humidity Operation Test	50°C, 85%, 300hrs	
Thermal Shock Test	-20℃~60℃, 1h/each cycle,100cycles	
Shock Test (Non-Operating)	50G,20ms,Half Sine Wave, (±X, ±Y,±Z)	
Vibration Test (Non-Operating)	1.5G ,10~200 Hz, x、y、z each axis/30min	
ESD test	Contact Discharge: ±8KV,150pF(330 Ω) ; Air Discharge: ±15KV,150pF(330 Ω)	1

Note1: ESD class C: Performance could be recovered by reset if temporary failure happened.

IVO	Info	昆山龙腾光电有限 SVision Optoelectronics(I	公司 Kunshan) Co.,LTI	D.	
Document ⁻	Document Title M101GWN9 R2 Product Information			Page No.	21/23	
Document No. Issue date 2013/07/1		2013/07/17	Revision	01		

11.0 Mechanical Characteristics

Figure 10 Reference Outline Drawing (Front Side)



Figure 11 Reference Outline Drawing (Back Side)





Document Title	M101GWN9 R2 Product Information				22/23
Document No.		Issue date	2013/07/17	Revision	01

12.0 Package Specification

TBD

13.0 Lot Mark

TBD

14.0 General Precaution

14.1 Use Restriction

In case of using the device for life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life-threatening or otherwise catastrophic, take into consideration that appropriate measures such as fail-safe functions and redundant system design should be taken.

14.2 Handling Precaution

- (1) Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. IVO does not warrant the module, if customers disassemble or modify the module.
- (2) If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid Crystal, and do not contact liquid crystal with skin. If liquid crystal contacts mouth or eyes, rinse out with water immediately. If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and Rinse thoroughly with water.
- (3) Disconnect power supply before handling LCD module
- (4) Refrain from strong mechanical shock and /or any force to the module.
- (5) Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature; etc otherwise LCD module may be damaged. It's recommended employing protection circuit for power supply.
- (6) Do not touch, push or rub the polarizer with anything harder than HB pencil lead. Use fingerstalls of soft gloves in order to keep clean display quality, when Persons handle the LCD module for incoming inspection or assembly.
- (7) When the surface is dusty, please wipe gently with absorbent cotton or other soft Material. When cleaning the adhesives, please use absorbent cotton wetted with a little Petroleum benzene or other adequate solvent.
- (8) Wipe off saliva or water drops as soon as possible. If saliva or water drops Contact with polarizer for a long time, they may causes deformation or color Fading.
- (9) Protection film must remove very slowly from the surface of LCD module to Prevent from electrostatic occurrence.
- (10) Because LCD module uses CMOS-IC on circuit board and TFT-LCD panel, it is Very weak to electrostatic discharge, Please be careful with electrostatic Discharge .Persons who handle the module should be grounded through adequate methods.

14.3 Storage Precaution

- (1) Please do not leave LCD module in the environment of high humidity and high temperature for a long time.
- (2) The module shall not be exposed under strong light such as direct sunlight.Otherwise, Display characteristics may be changed.
- (3) The module should be stored in a dark place. It is prohibited to apply sunlight or fluorescent light in storage.

IVO

昆山龙腾光电有限公司 InfoVision Optoelectronics (Kunshan) Co.,LTD.

Document Title	M101GWN9 R2 Product Information				23/23
Document No.		Issue date	2013/07/17	Revision	01

14.4 Operation Precaution

- (1) Do not connect or disconnect the module in the "Power On" condition.
- (2) Power supply should always be turned on/off by 9.0 "Power on/off sequence"
- (3) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference should be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (4) After installation of the TFT Module into an enclosure, do not twist nor bend the TFT Module even momentary. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.

14.5 Others

- (1) Ultra-violet ray filter is necessary for outdoor operation.
- (2) Avoid condensation of water which may result in improper operation or disconnection of electrode.
- (3) If the module keeps displaying the same pattern for a long period of time, the image may be "sticked" to the screen.
- (4) This module has its circuitry PCB's on the rear side and should be handled carefully in order not to be stressed.

14.6 Disposal

When disposing LCD module, obey the local environmental regulations.